

Why choose Uni Gas?

The UNI MP100 offers a simple, personal protection for a wide array of toxic gas and oxygen (O₂) measurement applications. In addition to common sensors such as carbon monoxide (CO), hydrogen sulfide (H₂S), nitrogen dioxide (NO₂), ammonia (NH₃) and sulfur dioxide (SO₂), we offer less-common sensors including chlorine (Cl₂), chlorine dioxide (ClO₂), phosgene (COCl₂), hydrogen chloride (HCl), arsine (AsH₃), phosphine (PH₃), ozone (O₃), methyl mercaptan and ethylene oxide.

Special oxygen monitors are available with long-life lead-free sensors or with inverted alarms for inert gas applications. The monitors have a large LCD providing maximum readability in the field and are made with six bright red LEDs allowing for quick alarm notification. Constructed of strong and durable material, the UNI is designed to be comfortable, yet drop-resistant. The UNI series can easily be bump tested and calibrated with the mPower CaliCase System.

Uni Single Gas Portable Detector

For detecting exotic gases

Feature, functions and benefits

- 50% larger (AA versus 2/3 AA) Lithium Battery
- Widest choice of sensors on the market
- Large display
- 50 Event data logging
- Low cost of ownership
- Smart sensors
- Solid stainless-steel alligator clip
- Durable housing
- Fast calibration & download using docking station
- UL Classification Class I, II, III, Groups ABCDEFG



Detector Specifications

Size	3.46 x 2.44 x 1.3 in (88 x 62 x 33 mm)
Weight	4.4 oz (125 g)
Sensors	Electrochemical
Response Time (t90)	15 seconds (CO/H2S/O2) Others vary, see individual sensor specifications in TA Note 4
Battery	Replaceable AA size Lithium battery, 3 years typical operation
Temperature	4°F to 122°F (-20°C to 50°C)
Humidity	5 to 95% relative humidity (non-condensing)
Alarm Type	High, Low, STEL & TWA alarms adjustable Over range alarm Low battery alarm
Alarm Signal	95 dB @ 30cm Bright red LEDds Built in vibration
Calibration	2-point calibration, zero and span, power on zero (user-selectable)
Event Log	Up to 50 alarm events
IR Rating	IP-67
EMI/RFI	EMC directive: 2014/30/EU
Safety Certifications	UL Class I, Div 1, Group ABCD Class II, Div 1, Group EFG Class III, Div 1 T4, -20°C ≤ Tamb ≤ +50°C IECEX Ex ia IIC T4 Ga ATEX II 1G Ex ia IIC T4 Ga
Sensor Life	CO & H2S expected operating life 5 years or longer, others 1 to 2 years as per warranty
Warranty	2 years on O2, CO, H2S, SO2, HCN, NO, NO2, and PH3 units including sensor; 1 year on others

Sensor Specifications

Gas	Range/Resolution PPM	Detector P/N
Carbon Monoxide (CO)	500/1	POR-UNI-CO
	1000/1	POR-UNI-HCO
	2000/1	POR-UNI-2CO
Hydrogen Sulphide (H2S)	50.0/0.1	POR-UNI-H2S
	100.0/0.1	POR-UNI-1H2s
	200.0/0.1	POR-UNI-2H2S
	1000/1	POR-UNI-HH2S
Oxygen (O2)	25/0.1%	M001-0032-000
	30/0.1%	POR-UNI-O2
Lead-free Oxygen (O2)	25/0.1%	POR-UNI-O2LL
	30/0.1%	M001-0095-000
Inerting Alarms (O2)	25/0.1%	M001-0093-000
Ammonia (NH3)	100/1	POR-UNI-NH3
	500/1	POR-UNI-HNH3
Arsine (AsH3)	1.00/0.01	POR-UNI-ASH3
Chlorine (CL2)	50.0/0.1	POR-UNI-CL2
Chlorine Dioxide (ClO2)	1.00/0.01	POR-UNI-CLO2
Phosgene (COCl2)	1.00/0.01	POR-UNI-COCL2
Hydrogen (H2)	1000/1	POR-UNI-H2
	2000/1	POR-UNI-2H2
Hydrogen Chloride (HCl)	15.0/0.1	POR-UNI-HCL
Hydrogen Fluoride (HF)	20.0/0.1	POR-UNI-HF
Hydrogen Cyanide (HCN)	100/0.1	POR-UNI-HCN
Nitric Oxide (NO)	250/1	POR-UNI-NO
Nitric Dioxide (NO2)	20.0/0.1	POR-UNI-NO2
Ozone (O3)	5.00/0.01	POR-UNI-O3
Phosphine (PH3)	20.00/0.01	POR-UNI-PH3
Sulphur Dioxide (SO2)	20.0/0.1	POR-UNI-SO2
	100.0/0.1	POR-UNI-HSO2
Acetaldehyde (C2H4O)	20.0/0.1	POR-UNI-C2H4O
Ethylene Oxide (ETO)	100.0/0.1	POR-UNI-ETO
	200.0/0.1	POR-UNI-HETO
Methyl Mercaptan (CH3SH)	10.0/0.1	POR-UNI-CH3SH
Tetrahydrothiophene (THT)	40.0/0.1	POR-UNI-THT

Due to ongoing research and product improvement, specifications are subject to change without notice.

Detector Accessories

Accessories	Description
Alligator, w/screw	N/A
Calibration/bump test adapter, w/tubing	N/A
External hydrophobic filter clips with filters for UNI (2 pcs each)	N/A
UNI Single Docking Station (MP100T)	For bump/cal and event logging. (requires separate demand-flow regulator and calibration gas)
CaliCase 4-UNI Docking Station (MP300T1)	For bump/cal and event logging. (requires separate calibration gas)

